



NOZZLES/MONITORS

PORTABLE/DECK GUN MONITOR

DESCRIPTION

This Buckeye monitor offers a dual capability. It can be positioned on the ground at a fire scene and left unattended to deliver high volumes of water or foam solution to the fire. It can also be mounted on a fire truck and used as a deck-gun. The BF-PM 1300 is manufactured from aluminum and has a full 3 1/4" waterway for low friction loss. The unit is easily adjusted and then locked in position. There is a safety stop at 35° above the horizontal plane. The vertical travel is controlled by adjustable hand wheel with worm gear drive fitted with grease zerk for easy lubrication. The unit is supplied complete with "stacked tips" and 3" flanged adaptor base. Using the interchangeable 3" flanged adaptor base, the unit can be mounted to a fire truck for flows up to 1,300 gpm (4,920 lpm.) It can then be demounted and returned to the portable base and used for ground applications.

FEATURES

BF-PM 1300

- Full 360° rotation - with truck mount and 254° rotation in portable mode.
- Inlet - Clappered 2 x 2 1/2" is Standard - 1 x 5" Storz (optional) - 1 x 4" Storz (optional) Stainless steel ball bearings at all rotation joints.
- Discharge 2 1/2" male NST.
- Red epoxy paint finish.
- Liquid filled pressure gauge.
- Grease fittings for lubrication.
- Titanium foldaway legs with carbon tips.

ORDERING INFORMATION

BFPM-1300

30 lbs. (14 kgs.)

